BOBRICK

Technical Data


# TrimLineSeries™ RECESSED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE

# B-39003

**Specify Finish Required**

☐ Stainless Steel, Satin Finish
☐ Matte Black Finish, please use model no. B-39003.MBLK






**Rough Wall Opening**

16" (405mm) wide

54-5/8" (1387mm) high

7-7/8" (200mm) minimum recessed depth


Distributed by
www.AmeraProducts.com
Phone: (800) 608-6568
Fax: (409) 840-5545
info@ameraproducts.com


**ADA/CBC Installation Guidance**

***Operable Part:** Top of paper towel dispenser opening

***Maximum mounting height of Operable Part:***

ADA/ICC: 48" maximum above finished floor (AFF)
CBC: 40" maximum above finished floor (AFF)

*For more information regarding operable parts, please refer to Bobrick Planning Guide for Accessible Restrooms, page 9.

## MATERIALS:

**Cabinet** — 18-8, type-304, heavy-gauge stainless steel. All-welded construction. Exposed surfaces have satin finish or matte black, as specified.

**Door** — 18-8, type-304, 18-gauge (1.2mm) stainless steel with satin finish or matte black, as specified. 9/16" (14mm) 90° return edges for maximum rigidity. Secured to cabinet with a concealed, full-length, stainless steel piano-hinge. Equipped with two tumbler locks keyed like other Bobrick washroom accessories. Tumbler locks flush with the door - no protrusion.

**Paper Towel Dispenser** — 18-8, type-304, 22-gauge (0.8mm) stainless steel with satin finish or matte black, as specified. Rounded towel tray has hemmed opening to dispense paper towels without tearing. Capacity: 600 C-fold, 800 multifold, or 1100 singlefold paper towels.

**TowelMate® Towel Rod Assembly —** Consisting of a round Nylon Rod and (2) stainless steel Rod Screws for attachment, is field replaceable. Stainless steel Stop Screws (2) lock TowelMate Rod assembly in place. To retrofit TowelMate into existing installed units manufactured prior to Feb. 2021, order TowelMate Accessory Bobrick Model No. 39003-130.

**Waste Container** — Removable, leakproof, rigid molded plastic. Capacity: 12-gal. (45.4-L).

continued . . .


The illustrations and descriptions herein are applicable to production as of the date of this Technical Data Sheet.
The manufacturer reserves the right to, and does from time to time, make changes and improvements in designs and dimensions.


Revised 6/28/23

© 2023 by Bobrick Washroom Equipment, Inc.

**OPERATION:**

Paper towel dispenser adjusts to accommodate C-fold, multifold, or singlefold paper towels by repositioning built-in adapter tabs in one of six slots. No additional towel trays or adapters required. Waste receptacle is serviced by opening door and removing waste container.

**INSTALLATION:**

Provide framed rough wall opening 16″ wide x 54-3/4″ high (405 x 1390mm). Minimum depth required from finish face of wall is 7-7/8″ (200mm). Allow clearance for construction features that may protrude into rough wall opening from opposite wall. Coordinate with mechanical engineer to avoid pipes, vents, and conduits. If unit projects above top of wainscot, provide aluminum channel or other filler to eliminate gap between flange and finish face of wall. Mount unit in wall opening with shims between framing and cabinet at all points indicated by an S, then secure unit with #8 x 1-1/4″ (4.2 x 32mm) sheet-metal screws (not furnished).

**SPECIFICATION:**

Recessed paper towel dispenser and waste receptacle shall be type-304 stainless steel with all-welded construction; exposed surfaces shall have satin finish or matte black, as specified. Unit equipped with TowelMate consisting of a 90° return towel guide angle inside cabinet to prevent paper towels from falling forward out when door is opened for servicing and a Nylon Rod across the center of the towel tray to dispense paper towels one at a time. Door shall be 18 gauge (1.2mm); have 9/16″ (14mm) 90° return edges; be secured to cabinet with a concealed, full-length, stainless steel piano-hinge; and equipped with two tumbler locks keyed like other Bobrick washroom accessories. Tumbler locks flush with the door - no protrusion. Paper towel dispenser shall be equipped with a six-position adapter that is adjustable to dispense 600 C-fold, 800 multifold, or 1100 singlefold paper towels. Waste receptacle shall be furnished with a removable, leakproof, rigid molded plastic waste-container with a minimum capacity of 12-gal. (45.4-L).

**Recessed Paper Towel Dispenser And Waste Receptacle**

Distributed by
www.AmeraProducts.com
Phone: (800) 608-6568
Fax: (409) 840-5545
info@ameraproducts.com

The illustrations and descriptions herein are applicable to production as of the date of this Technical Data Sheet.
The manufacturer reserves the right to, and does from time to time, make changes and improvements in designs and dimensions.

B-39003 r6/28/23
© 2023 by Bobrick Washroom Equipment, Inc.